United States Patent [19]			[11] Patent Number: 5,025,787	
Sutherland et al.			[45] Date of Patent: Jun. 25, 1991	
[54]	INTRAUT	ERINE PROBE	3,545,432 12/1970 Berman	
[75]	Inventors:	Ian A. Sutherland, Harpenden; Nigel J. Randall, London; Philip J. Steer, Kingston upon Thames, all of England	4,082,087 4/1978 Howson . 4,141,365 2/1979 Fischell et al 4,211,237 6/1980 Nagel	
[73]	Assignee:	The Imperial College of Science, Technology & Medicine, London,	FOREIGN PATENT DOCUMENTS 0206248 12/1986 European Pat. Off.	
[21] [22]	Appl. No.:	England 484,956 Feb. 26, 1990	Primary Examiner—William E. Kamm Assistant Examiner—Kevin Pontius Attorney, Agent, or Firm—Sughrue, Mion, Zinn, Macpeak & Seas	
	Dala	ited U.S. Application Data	[57] ABSTRACT	
[63] Continuation-in-part of Ser. No. 330,020, Mar. 29, 1989, abandoned, and Ser. No. 346,971, Jun. 6, 1989, abandoned.		on-in-part of Ser. No. 330,020, Mar. 29, doned, and Ser. No. 346,971, Jun. 6, 1989,	A method of and apparatus for monitoring the condi- tion of a fetus during labor includes an elongated flexi- ble, flattened body member formed from an electrically insulating material having a rounded distal end and	
[30]	[30] Foreign Application Priority Data		having at least oen sensor mounted in a flat face of the	
Mar. 29, 1988 [GB]       United Kingdom			body member. The body member is sufficiently directionally stable to be insertable into the vaginal tract and through the cervix and is capable of being guided	
[51] [52]		around the fetus without twisting. The body member has a bending stiffness about an axis transverse to the plane of the body member of between 1 and 10 mega-		
[58]	[58] Field of Search 128/639, 642, 698, 748, 128/775		Newtons/m <sup>2</sup> . Once the apparatus is introduced into the cervix, the signal ouptut from at least one electrode is	
[56]	U.S.	References Cited PATENT DOCUMENTS	analyzed by discriminating the fetal heart rate from the maternal heart rate.	